

Gamma's EPDM cold shrink is specially formulated pre expanded rubber shrink tube that does not require heat to shrink. It is supplied expanded over an easily removable plastic cylinder. When the plastic cord is pulled, it allows the rubber tubing to shrink and rapidly seal and protect the connector, while gripping tight around the cable.

These cold shrink kits are a safe, easy and reliable method to seal coaxial connections.

EPDM cold shrink kits are ideal for wireless communication towers and any other exposed coax interface. They are applied without flame and installed without tools. Once installed correctly, the connection is weather proof and protected against dust or dirt that may find its way into your connection.



Features

- Simple installation, requires only workman's hands
- No torch or heat source required for installation
- Good thermal stability
- Seals tight, retains its resiliency and pressure even after prolonged years of aging and exposure
- Waterproof
- Resisting to fungus, acids, alkalis, ozone and ultraviolet light
- Accommodates a wide range of cables
- Excellent wet electrical properties



EPDM Cold Shrink

Specifications

Gamma's Cold Shrink Kit contains EPDM rubber sleeves that are applied without a heat gun or flame. It's compatible with the coax cables and N or 7/16 DIN connectors. It's an open-ended, tubular rubber sleeve that are factory expanded and assembled onto a removable core. They are supplied for field installation in the pre-stretched condition.

Ordering Information

General EPDM					High Shrinkage EPDM				
Part Number	Size	Before Recovery (mm)	After Recovery (mm)	Color	Part Number	Size	Before Recovery (mm)	After Recovery (mm)	Color
EPDM-8320-6	Ø 20	8-15	152	Black	EPDM-8435-L	Ø 35	12.5-30	229-279	Black
EPDM-8325-L	Ø 25	10-20	203-280	Black	EPDM-8440-L	Ø 40	14-33	152-406	Black
EPDM-8335-L	Ø 35	14-30	229-280	Black	EPDM-8453-L	Ø 53	19-46	152-457	Black
EPDM-8340-L	Ø 40	17.5-33	152-457	Black	EPDM-8460-10	Ø 60	20.5-51	254	Black
EPDM-8353-L	Ø 53	25-46	152-457	Black	EPDM-8470-L	Ø 70	25-63	152-457	Black
EPDM-8370-L	Ø 70	32-63	152-457	Black	EPDM-8480-13	Ø 80	27.4-70	325	Black
EPDM-8104-9	Ø 104	43-94	229	Black					

L indicates the required length after relaxed with the unit of mm or inch

RoHS : compliant with EU RoHS Directive (2005/95/EC)

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under RoHS. This information represents GAMMA'S knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to GAMMA.

Property of Gamma Electronics Inc.

2818 Metropolitan Place, Suite A
Pomona, CA 91767
www.gammaelectronics.net